

AMENDATORY SECTION (Amending WSR 21-24-059, filed 11/29/21, effective 12/30/21)

**WAC 173-400-025 Adoption by reference.** (1) Adoption by reference date: ((December 23, 2020)) August 24, 2022.

(2) Federal rules mentioned in this rule are adopted as they exist on the date in subsection (1) of this section. Adoption by reference means the federal rule applies as if it was copied into this rule.

AMENDATORY SECTION (Amending WSR 18-17-111, filed 8/16/18, effective 9/16/18)

**WAC 173-400-050 Emission standards for combustion and incineration units.** (1) Combustion and incineration emissions units must meet all requirements of WAC 173-400-040 and, in addition, no person shall cause or allow emissions of particulate matter in excess of 0.23 gram per dry cubic meter at standard conditions (0.1 grain/dscf), except, for an emissions unit combusting waste wood for the production of steam. No person shall allow the emission of particulate matter in excess of 0.46 gram per dry cubic meter at standard conditions (0.2 grain/dscf), as measured by 40 C.F.R. Part 60, Appendix A, Test Method 5 (in effect on the date in WAC 173-400-025) or approved procedures in *Source Test Manual - Procedures for Compliance Testing*, state of Washington, department of ecology, as of September 20, 2004, on file at ecology.

(2) For any incinerator, no person shall cause or allow emissions in excess of one hundred ppm of total carbonyls as measured by Source Test Method 14 procedures in *Source Test Manual - Procedures for Compliance Testing*, state of Washington, department of ecology, as of September 20, 2004, on file at ecology. An applicable EPA reference method or other procedures to collect and analyze for the same compounds collected in the ecology method may be used if approved by the permitting authority prior to its use.

(a) **Incinerators** not subject to the requirements of chapter 173-434 WAC or WAC 173-400-050 (4) or (5), or requirements in WAC 173-400-075 (40 C.F.R. Part 63, Subpart EEE in effect on the date in WAC 173-400-025) and WAC 173-400-115 (40 C.F.R. Part 60, Subparts E, Ea, Eb, Ec, AAAA, and CCCC (in effect on the date in WAC 173-400-025)) shall be operated only during daylight hours unless written permission to operate at other times is received from the permitting authority.

(b) Total carbonyls means the concentration of organic compounds containing the =C=O radical as collected by Source Test Method 14 procedures in *Source Test Manual - Procedures for Compliance Testing*, state of Washington, department of ecology, as of September 20, 2004, on file at ecology.

(3) Measured concentrations for combustion and incineration units shall be adjusted for volumes corrected to seven percent oxygen, except when the permitting authority determines that an alternate oxygen correction factor is more representative of normal operations such as the correction factor included in an applicable NSPS or NESHAP, actual operating characteristics, or the manufacturer's specifications for the emission unit.

(4) **Commercial and industrial solid waste incineration units** constructed on or before November 30, 1999. A commercial and industrial solid waste incineration unit that commenced construction on or before November 30, 1999, that meets the applicability requirements in 40 C.F.R. 62.14510, must comply with the requirements in 40 C.F.R. Part 62, Subpart GGG (in effect on the date in WAC 173-400-025).

Note: Subsection (2) of this section (a state-only provision) does not apply to a unit subject to this subsection because this ~~((section))~~ subsection is ~~((based-on))~~ a federal requirement~~((s))~~.

(a) Definitions.

(i) "Commercial and industrial solid waste incineration (CISWI) unit" means any combustion device that combusts commercial and industrial waste, as defined in this subsection. The boundaries of a CISWI unit are defined as, but not limited to, the commercial or industrial solid waste fuel feed system, grate system, flue gas system, and bottom ash. The CISWI unit does not include air pollution control equipment or the stack. The CISWI unit boundary starts at the commercial and industrial solid waste hopper (if applicable) and extends through two areas:

(A) The combustion unit flue gas system, which ends immediately after the last combustion chamber.

(B) The combustion unit bottom ash system, which ends at the truck loading station or similar equipment that transfers the ash to final disposal. It includes all ash handling systems connected to the bottom ash handling system.

(ii) "Commercial and industrial solid waste" means solid waste combusted in an enclosed device using controlled flame combustion without energy recovery that is a distinct operating unit of any commercial or industrial facility (including field erected, modular, and custom built incineration units operating with starved or excess air), or solid waste combusted in an air curtain incinerator without energy recovery that is a distinct operating unit of any commercial or industrial facility.

(b) Applicability. This section applies to incineration units that meet all three criteria:

(i) The incineration unit meets the definition of CISWI unit in this subsection.

(ii) The incineration unit commenced construction on or before November 30, 1999.

(iii) The incineration unit is not exempt under (c) of this subsection.

(c) The following types of incineration units are exempt from this subsection:

(i) *Pathological waste incineration units.* Incineration units burning 90 percent or more by weight (on a calendar quarter basis and excluding the weight of auxiliary fuel and combustion air) of pathological waste, low-level radioactive waste, and/or chemotherapeutic waste as defined in 40 C.F.R. 60.2265 (in effect on the date in WAC 173-400-025) are not subject to this section if you meet the two requirements specified in (c)(i)(A) and (B) of this subsection.

(A) Notify the permitting authority that the unit meets these criteria.

(B) Keep records on a calendar quarter basis of the weight of pathological waste, low-level radioactive waste, and/or chemotherapeutic waste burned, and the weight of all other fuels and wastes burned in the unit.

(ii) *Agricultural waste incineration units.* Incineration units burning 90 percent or more by weight (on a calendar quarter basis and

excluding the weight of auxiliary fuel and combustion air) of agricultural wastes as defined in 40 C.F.R. 60.2265 (in effect on the date in WAC 173-400-025) are not subject to this section if you meet the two requirements specified in (c)(ii)(A) and (B) of this subsection.

(A) Notify the permitting authority that the unit meets these criteria.

(B) Keep records on a calendar quarter basis of the weight of agricultural waste burned, and the weight of all other fuels and wastes burned in the unit.

(iii) *Municipal waste combustion units.* Incineration units that meet either of the two criteria specified in (c)(iii)(A) and (B) of this subsection.

(A) Units are regulated under 40 C.F.R. Part 60, Subpart Ea or Subpart Eb (in effect on the date in WAC 173-400-025); Spokane County Air Pollution Control Authority Regulation 1, Section 6.17 (in effect on February 13, 1999); 40 C.F.R. Part 60, Subpart AAAA (in effect on the date in WAC 173-400-025); or WAC 173-400-050(5).

(B) Units burn greater than 30 percent municipal solid waste or refuse-derived fuel, as defined in 40 C.F.R. Part 60 (in effect on the date in WAC 173-400-025), Subparts Ea, Eb, and AAAA, and WAC 173-400-050(5), and that have the capacity to burn less than 35 tons (32 megagrams) per day of municipal solid waste or refuse-derived fuel, if you meet the two requirements in (c)(iii)(B)(I) and (II) of this subsection.

(I) Notify the permitting authority that the unit meets these criteria.

(II) Keep records on a calendar quarter basis of the weight of municipal solid waste burned, and the weight of all other fuels and wastes burned in the unit.

(iv) *Medical waste incineration units.* Incineration units regulated under 40 C.F.R. Part 60, Subpart Ec (Standards of Performance for Hospital/Medical/Infectious Waste Incinerators for Which Construction is Commenced After June 20, 1996) (in effect on the date in WAC 173-400-025);

(v) *Small power production facilities.* Units that meet the three requirements specified in (c)(v)(A) through (C) of this subsection.

(A) The unit qualifies as a small power-production facility under section 3 (17)(C) of the Federal Power Act (16 U.S.C. 796 (17)(C)).

(B) The unit burns homogeneous waste (not including refuse-derived fuel) to produce electricity.

(C) You notify the permitting authority that the unit meets all of these criteria.

(vi) *Cogeneration facilities.* Units that meet the three requirements specified in (c)(vi)(A) through (C) of this subsection.

(A) The unit qualifies as a cogeneration facility under section 3 (18)(B) of the Federal Power Act (16 U.S.C. 796 (18)(B)).

(B) The unit burns homogeneous waste (not including refuse-derived fuel) to produce electricity and steam or other forms of energy used for industrial, commercial, heating, or cooling purposes.

(C) You notify the permitting authority that the unit meets all of these criteria.

(vii) *Hazardous waste combustion units.* Units that meet either of the two criteria specified in (c)(vii)(A) or (B) of this subsection.

(A) Units for which you are required to get a permit under section 3005 of the Solid Waste Disposal Act.

(B) Units regulated under 40 C.F.R. Part 63, Subpart EEE (National Emission Standards for Hazardous Air Pollutants from Hazardous Waste Combustors) (in effect on the date in WAC 173-400-025).

(viii) *Materials recovery units*. Units that combust waste for the primary purpose of recovering metals, such as primary and secondary smelters;

(ix) *Air curtain incinerators*. Air curtain incinerators that burn only the materials listed in (c)(ix)(A) through (C) of this subsection are only required to meet the requirements under "Air Curtain Incinerators" in 40 C.F.R. 60.2245 through 60.2260 (in effect on the date in WAC 173-400-025).

(A) 100 percent wood waste, as defined in 40 C.F.R. 60.2265.

(B) 100 percent clean lumber.

(C) 100 percent mixture of only wood waste, clean lumber, and/or yard waste, as these terms are defined in 40 C.F.R. 60.2265.

(x) *Cyclonic barrel burners*. See 40 C.F.R. 60.2265 (in effect on the date in WAC 173-400-025).

(xi) *Rack, part, and drum reclamation units*. See 40 C.F.R. 60.2265 (in effect on the date in WAC 173-400-025).

(xii) *Cement kilns*. Kilns regulated under 40 C.F.R. Part 63, Subpart LLL (National Emission Standards for Hazardous Air Pollutants from the Portland Cement Manufacturing Industry) (in effect on the date in WAC 173-400-025).

(xiii) *Sewage sludge incinerators*. Incineration units regulated under 40 C.F.R. Part 60, Subpart O (Standards of Performance for Sewage Treatment Plants) (in effect on the date in WAC 173-400-025).

(xiv) *Chemical recovery units*. Combustion units burning materials to recover chemical constituents or to produce chemical compounds where there is an existing commercial market for such recovered chemical constituents or compounds. The seven types of units described in (c)(xiv)(A) through (G) of this subsection are considered chemical recovery units.

(A) Units burning only pulping liquors (i.e., black liquor) that are reclaimed in a pulping liquor recovery process and reused in the pulping process.

(B) Units burning only spent sulfuric acid used to produce virgin sulfuric acid.

(C) Units burning only wood or coal feedstock for the production of charcoal.

(D) Units burning only manufacturing by-product streams/residues containing catalyst metals which are reclaimed and reused as catalysts or used to produce commercial grade catalysts.

(E) Units burning only coke to produce purified carbon monoxide that is used as an intermediate in the production of other chemical compounds.

(F) Units burning only hydrocarbon liquids or solids to produce hydrogen, carbon monoxide, synthesis gas, or other gases for use in other manufacturing processes.

(G) Units burning only photographic film to recover silver.

(xv) *Laboratory analysis units*. Units that burn samples of materials for the purpose of chemical or physical analysis.

(d) Exceptions.

(i) Physical or operational changes to a CISWI unit made primarily to comply with this section do not qualify as a "modification" or "reconstruction" (as defined in 40 C.F.R. 60.2815) (in effect on the date in WAC 173-400-025).

(ii) Changes to a CISWI unit made on or after June 1, 2001, that meet the definition of "modification" or "reconstruction" as defined in 40 C.F.R. 60.2815 (in effect on the date in WAC 173-400-025) mean the CISWI unit is considered a new unit and subject to WAC 173-400-115, which adopts 40 C.F.R. Part 60, Subpart CCCC (in effect on the date in WAC 173-400-025).

(e) A CISWI unit must comply with 40 C.F.R. 60.2575 through 60.2875 (in effect on the date in WAC 173-400-025). The federal rule contains these major components:

- Increments of progress towards compliance in 60.2575 through 60.2630;

- Waste management plan requirements in 60.2620 through 60.2630;

- Operator training and qualification requirements in 60.2635 through 60.2665;

- Emission limitations and operating limits in 60.2670 through 60.2685;

- Performance testing requirements in 60.2690 through 60.2725;

- Initial compliance requirements in 60.2700 through 60.2725;

- Continuous compliance requirements in 60.2710 through 60.2725;

- Monitoring requirements in 60.2730 through 60.2735;

- Recordkeeping and reporting requirements in 60.2740 through 60.2800;

- Title V operating permits requirements in 60.2805;

- Air curtain incinerator requirements in 60.2810 through 60.2870;

- Definitions in 60.2875; and

- Tables in 60.2875. In Table 1, the final control plan must be submitted before June 1, 2004, and final compliance must be achieved by June 1, 2005.

(i) Exception to adopting the federal rule. For purposes of this section, "administrator" includes the permitting authority.

(ii) Exception to adopting the federal rule. For purposes of this section, "you" means the owner or operator.

(iii) Exception to adopting the federal rule. For purposes of this section, each reference to "the effective date of state plan approval" means July 1, 2002.

(iv) Exception to adopting the federal rule. The Title V operating permit requirements in 40 C.F.R. 60.2805(a) are not adopted. Each CISWI unit, regardless of whether it is a major or nonmajor unit, is subject to the air operating permit regulation, chapter 173-401 WAC, beginning on July 1, 2002. See WAC 173-401-500 for the permit application requirements and deadlines.

(v) Exception to adopting the federal rule. The following compliance dates apply:

(A) The final control plan (Increment 1) must be submitted no later than July 1, 2003. (See Increment 1 in Table 1.)

(B) Final compliance (Increment 2) must be achieved no later than July 1, 2005. (See Increment 2 in Table 1.)

(5) **Small municipal waste combustion units** constructed on or before August 30, 1999. A small municipal waste combustion unit constructed on or before August 30, 1999, that meets the applicability requirements in 40 C.F.R. 62.14510, must comply with the requirements in 40 C.F.R. Part 62, Subpart JJJ (in effect on the date in WAC 173-400-025).

(a) Definition. "Municipal waste combustion unit" means any setting or equipment that combusts, liquid, or gasified municipal solid waste including, but not limited to, field-erected combustion units

(with or without heat recovery), modular combustion units (starved air- or excess-air), boilers (for example, steam generating units), furnaces (whether suspension-fired, grate-fired, mass-fired, air-curtain incinerators, or fluidized bed-fired), and pyrolysis/combustion units. Two criteria further define municipal waste combustion units:

(i) Municipal waste combustion units do not include the following units:

(A) Pyrolysis or combustion units located at a plastics or rubber recycling unit as specified under the exemptions in this subsection (5)(c)(viii) and (ix).

(B) Cement kilns that combust municipal solid waste as specified under the exemptions in this subsection (5)(c)(x).

(C) Internal combustion engines, gas turbines, or other combustion devices that combust landfill gases collected by landfill gas collection systems.

(ii) The boundaries of a municipal waste combustion unit are defined as follows. The municipal waste combustion unit includes, but is not limited to, the municipal solid waste fuel feed system, grate system, flue gas system, bottom ash system, and the combustion unit water system. The municipal waste combustion unit does not include air pollution control equipment, the stack, water treatment equipment, or the turbine-generator set. The municipal waste combustion unit boundary starts at the municipal solid waste pit or hopper and extends through three areas:

(A) The combustion unit flue gas system, which ends immediately after the heat recovery equipment or, if there is no heat recovery equipment, immediately after the combustion chamber.

(B) The combustion unit bottom ash system, which ends at the truck loading station or similar equipment that transfers the ash to final disposal. It includes all ash handling systems connected to the bottom ash handling system.

(C) The combustion unit water system, which starts at the feed water pump and ends at the piping that exits the steam drum or superheater.

(b) Applicability. This section applies to a municipal waste combustion unit that meets these three criteria:

(i) The municipal waste combustion unit has the capacity to combust at least 35 tons per day of municipal solid waste but no more than 250 tons per day of municipal solid waste or refuse-derived fuel.

(ii) The municipal waste combustion unit commenced construction on or before August 30, 1999.

(iii) The municipal waste combustion unit is not exempt under (c) of this section.

(c) Exempted units. The following municipal waste combustion units are exempt from the requirements of this section:

(i) *Small municipal waste combustion units that combust less than 11 tons per day.* Units are exempt from this section if four requirements are met:

(A) The municipal waste combustion unit is subject to a federally enforceable order or order of approval limiting the amount of municipal solid waste combusted to less than 11 tons per day.

(B) The owner or operator notifies the permitting authority that the unit qualifies for the exemption.

(C) The owner or operator of the unit sends a copy of the federally enforceable order or order of approval to the permitting authority.

(D) The owner or operator of the unit keeps daily records of the amount of municipal solid waste combusted.

(ii) *Small power production units.* Units are exempt from this section if four requirements are met:

(A) The unit qualifies as a small power production facility under section 3 (17)(C) of the Federal Power Act (16 U.S.C. 796 (17)(C)).

(B) The unit combusts homogeneous waste (excluding refuse-derived fuel) to produce electricity.

(C) The owner or operator notifies the permitting authority that the unit qualifies for the exemption.

(D) The owner or operator submits documentation to the permitting authority that the unit qualifies for the exemption.

(iii) *Cogeneration units.* Units are exempt from this section if four requirements are met:

(A) The unit qualifies as a small power production facility under section 3 (18)(C) of the Federal Power Act (16 U.S.C. 796 (18)(C)).

(B) The unit combusts homogeneous waste (excluding refuse-derived fuel) to produce electricity and steam or other forms of energy used for industrial, commercial, heating, or cooling purposes.

(C) The owner or operator notifies the permitting authority that the unit qualifies for the exemption.

(D) The owner or operator submits documentation to the permitting authority that the unit qualifies for the exemption.

(iv) *Municipal waste combustion units that combust only tires.* Units are exempt from this section if three requirements are met:

(A) The municipal waste combustion unit combusts a single-item waste stream of tires and no other municipal waste (the unit can co-fire coal, fuel oil, natural gas, or other nonmunicipal solid waste).

(B) The owner or operator notifies the permitting authority that the unit qualifies for the exemption.

(C) The owner or operator submits documentation to the permitting authority that the unit qualifies for the exemption.

(v) *Hazardous waste combustion units.* Units are exempt from this section if the units have received a permit under section 3005 of the Solid Waste Disposal Act.

(vi) *Materials recovery units.* Units are exempt from this section if the units combust waste mainly to recover metals. Primary and secondary smelters may qualify for the exemption.

(vii) *Cofired units.* Units are exempt from this section if four requirements are met:

(A) The unit has a federally enforceable order or order of approval limiting municipal solid waste combustion to no more than 30 percent of total fuel input by weight.

(B) The owner or operator notifies the permitting authority that the unit qualifies for the exemption.

(C) The owner or operator submits a copy of the federally enforceable order or order of approval to the permitting authority.

(D) The owner or operator records the weights, each quarter, of municipal solid waste and of all other fuels combusted.

(viii) *Plastics/rubber recycling units.* Units are exempt from this section if four requirements are met:

(A) The pyrolysis/combustion unit is an integrated part of a plastics/rubber recycling unit as defined in 40 C.F.R. 60.1940 (in effect on the date in WAC 173-400-025).

(B) The owner or operator of the unit records the weight, each quarter, of plastics, rubber, and rubber tires processed.

(C) The owner or operator of the unit records the weight, each quarter, of feed stocks produced and marketed from chemical plants and petroleum refineries.

(D) The owner or operator of the unit keeps the name and address of the purchaser of the feed stocks.

(ix) *Units that combust fuels made from products of plastics/rubber recycling plants.* Units are exempt from this section if two requirements are met:

(A) The unit combusts gasoline, diesel fuel, jet fuel, fuel oils, residual oil, refinery gas, petroleum coke, liquefied petroleum gas, propane, or butane produced by chemical plants or petroleum refineries that use feed stocks produced by plastics/rubber recycling units.

(B) The unit does not combust any other municipal solid waste.

(x) *Cement kilns.* Cement kilns that combust municipal solid waste are exempt.

(xi) *Air curtain incinerators.* If an air curtain incinerator as defined under 40 C.F.R. 60.1910 combusts 100 percent yard waste, then those units must only meet the requirements under 40 C.F.R. 60.1910 through 60.1930 (in effect on the date in WAC 173-400-025).

(d) Exceptions.

(i) Physical or operational changes to an existing municipal waste combustion unit made primarily to comply with this section do not qualify as a modification or reconstruction, as those terms are defined in 40 C.F.R. 60.1940 (in effect on the date in WAC 173-400-025).

(ii) Changes to an existing municipal waste combustion unit made on or after June 6, 2001, that meet the definition of modification or reconstruction, as those terms are defined in 40 C.F.R. 60.1940 (in effect on the date in WAC 173-400-025), mean the unit is considered a new unit and subject to WAC 173-400-115, which adopts 40 C.F.R. Part 60, Subpart AAAA (in effect on the date in WAC 173-400-025).

(e) Municipal waste combustion units are divided into two subcategories based on the aggregate capacity of the municipal waste combustion plant as follows:

(i) Class I units. Class I units are small municipal waste combustion units that are located at municipal waste combustion plants with an aggregate plant combustion capacity greater than 250 tons per day of municipal solid waste. See the definition of "municipal waste combustion plant capacity" in 40 C.F.R. 60.1940 (in effect on the date in WAC 173-400-025) for the specification of which units are included in the aggregate capacity calculation.

(ii) Class II units. Class II units are small municipal waste combustion units that are located at municipal waste combustion plants with an aggregate plant combustion capacity less than or equal to 250 tons per day of municipal solid waste. See the definition of "municipal waste combustion plant capacity" in 40 C.F.R. 60.1940 (in effect on the date in WAC 173-400-025) for the specification of which units are included in the aggregate capacity calculation.

(f) Compliance option 1.

(i) A municipal solid waste combustion unit may choose to reduce, by the final compliance date of June 1, 2005, the maximum combustion capacity of the unit to less than 35 tons per day of municipal solid waste. The owner or operator must submit a final control plan and the notifications of achievement of increments of progress as specified in 40 C.F.R. 60.1610 (in effect on the date in WAC 173-400-025).

(ii) The final control plan must, at a minimum, include two items:



(A) A description of the physical changes that will be made to accomplish the reduction.

(B) Calculations of the current maximum combustion capacity and the planned maximum combustion capacity after the reduction. Use the equations specified in 40 C.F.R. 60.1935 (d) and (e) (in effect on the date in WAC 173-400-025) to calculate the combustion capacity of a municipal waste combustion unit.

(iii) An order or order of approval containing a restriction or a change in the method of operation does not qualify as a reduction in capacity. Use the equations specified in 40 C.F.R. 60.1935 (d) and (e) (in effect on the date in WAC 173-400-025) to calculate the combustion capacity of a municipal waste combustion unit.

(g) Compliance option 2. The municipal waste combustion unit must comply with 40 C.F.R. 60.1585 through 60.1905, and 60.1935 (in effect on the date in WAC 173-400-025).

(i) The rule contains these major components:

(A) Increments of progress towards compliance in 60.1585 through 60.1640;

(B) Good combustion practices - Operator training in 60.1645 through 60.1670;

(C) Good combustion practices - Operator certification in 60.1675 through 60.1685;

(D) Good combustion practices - Operating requirements in 60.1690 through 60.1695;

(E) Emission limits in 60.1700 through 60.1710;

(F) Continuous emission monitoring in 60.1715 through 60.1770;

(G) Stack testing in 60.1775 through 60.1800;

(H) Other monitoring requirements in 60.1805 through 60.1825;

(I) Recordkeeping reporting in 60.1830 through 60.1855;

(J) Reporting in 60.1860 through 60.1905;

(K) Equations in 60.1935;

(L) Tables 2 through 8.

(ii) Exception to adopting the federal rule. For purposes of this section, each reference to the following is amended in the following manner:

(A) "State plan" in the federal rule means WAC 173-400-050(5).

(B) "You" in the federal rule means the owner or operator.

(C) "Administrator" includes the permitting authority.

(D) "The effective date of the state plan approval" in the federal rule means December 6, 2002.

(h) Compliance schedule.

(i) Small municipal waste combustion units must achieve final compliance or cease operation not later than December 1, 2005.

(ii) Small municipal waste combustion units must achieve compliance by May 6, 2005, for all Class II units, and by November 6, 2005, for all Class I units.

(iii) Class I units must comply with these additional requirements:

(A) The owner or operator must submit the dioxins/furans stack test results for at least one test conducted during or after 1990. The stack test must have been conducted according to the procedures specified under 40 C.F.R. 60.1790 (in effect on the date in WAC 173-400-025).

(B) Class I units that commenced construction after June 26, 1987, must comply with the dioxins/furans and mercury limits specified in Tables 2 and 3 in 40 C.F.R. Part 60, Subpart BBBBB (in effect on the date in WAC 173-400-025) by the later of two dates:

(I) December 6, 2003; or

(II) One year following the issuance of an order of approval (revised construction approval or operation permit) if an order or order of approval or operation modification is required.

(i) Air operating permit. Applicability to chapter 173-401 WAC, the air operating permit regulation, begins on July 1, 2002. See WAC 173-401-500 for the permit application requirements and deadlines.

(6) **Hazardous/medical/infectious waste incinerators** constructed on or before December 1, 2008. Hospital/medical/infectious waste incinerators constructed on or before December 1, 2008, must comply with the requirements in 40 C.F.R. Part 62, Subpart HHH (in effect on the date in WAC 173-400-025).

AMENDATORY SECTION (Amending WSR 18-17-111, filed 8/16/18, effective 9/16/18)

**WAC 173-400-070 Emission standards for certain source categories.** Ecology finds that the reasonable regulation of sources within certain categories requires separate standards applicable to such categories. The standards set forth in this section shall be the maximum allowable standards for emissions units within the categories listed. Except as specifically provided in this section, such emissions units shall not be required to meet the provisions of WAC 173-400-040, 173-400-050 and 173-400-060.

(1) **Wigwam and silo burners.** As of January 1, 2020, it is illegal to use a wigwam or silo burner in Washington. A wigwam or silo burner may operate until midnight December 31, 2019, provided it complies with the following:

(a) All wigwam and silo burners designed to dispose of waste wood must meet all provisions of WAC 173-400-040 (2), (3), (4), (5), (6), (7), (8), and WAC 173-400-050(4), 173-400-115, or 40 C.F.R. Part 62, Subpart III in effect on the date in WAC 173-400-025 as applicable.

(b) All wigwam and silo burners must use RACT. All emissions units shall be operated and maintained to minimize emissions. These requirements may include a controlled tangential vent overfire air system, an adequate underfire system, elimination of all unnecessary openings, a controlled feed and other modifications determined necessary by ecology or the permitting authority.

(c) It shall be unlawful to install or increase the existing use of any burner that does not meet all requirements for new sources including those requirements specified in WAC 173-400-040 and 173-400-050, except operating hours.

(d) The permit authority may establish additional requirements for wigwam and silo burners. These requirements may include, but shall not be limited to:

(i) A requirement to meet all provisions of WAC 173-400-040 and 173-400-050. Wigwam and silo burners will be considered to be in compliance if they meet the requirements contained in WAC 173-400-040(2), visible emissions.

(ii) A requirement to apply BACT.

(iii) A requirement to reduce or eliminate emissions if ecology establishes that such emissions unreasonably interfere with the use and enjoyment of the property of others or are a cause of violation of ambient air standards.

(2) **Hog fuel boilers.**

(a) Hog fuel boilers shall meet all provisions of WAC 173-400-040 and 173-400-050(1).

(b) All hog fuel boilers shall utilize RACT and shall be operated and maintained to minimize emissions.

(3) **Orchard heating.**

(a) Burning of rubber materials, asphaltic products, crankcase oil or petroleum wastes, plastic, or garbage is prohibited.

(b) This provision is in effect until the effective date of EPA's removal of the September 20, 1993, version of WAC 173-400-107 from the SIP. It is unlawful to burn any material or operate any orchard-heating device that causes a visible emission exceeding twenty percent opacity, except during the first thirty minutes after such device or material is ignited.

(c) This provision takes effect on the effective date of EPA's removal of the September 20, 1993, version of WAC 173-400-107 from the SIP. It is unlawful to burn any material or operate an orchard-heating device that causes a visible emission exceeding twenty percent opacity as specified in WAC 173-400-040(2).

(4) **Grain elevators.** Any grain elevator which is primarily classified as a materials handling operation shall meet all the provisions of WAC 173-400-040 (2), (3), (4), and (5).

(5) **Other waste wood burners.**

(a) Waste wood burners not specifically provided for in this section shall meet all applicable provisions of:

(i) WAC 173-400-040 and 173-400-050;

(ii) 40 C.F.R. Part 60, Subpart CCCC (in effect on the date in WAC 173-400-025); and

(iii) 40 C.F.R. Part 62, Subpart III (in effect on the date in WAC 173-400-025).

(b) Such waste wood burners shall utilize RACT and shall be operated and maintained to minimize emissions.

(6) **Municipal solid waste landfills constructed, reconstructed, or modified before May 30, 1991.** A municipal solid waste landfill that commenced construction prior to May 30, 1991, and has not been modified or reconstructed since May 30, 1991, must comply with the requirements in 40 C.F.R. Part 62, Subpart GGG (in effect on the date in WAC 173-400-025). A municipal solid waste landfill (MSW landfill) is an entire disposal facility in a contiguous geographical space where household waste is placed in or on the land. A MSW landfill may also receive other types of waste regulated under Subtitle D of the Federal Resource Conservation and Recovery Act including the following: Commercial solid waste, nonhazardous sludge, conditionally exempt small quantity generator waste, and industrial solid waste. Portions of an MSW landfill may be separated by access roads. A MSW landfill may be either publicly or privately owned. A MSW landfill may be a new MSW landfill, an existing MSW landfill, or a lateral expansion. All references in this subsection to 40 C.F.R. Part 60 rules mean those rules in effect on the date in WAC 173-400-025.

(a) Applicability. These rules apply to each MSW landfill constructed, reconstructed, or modified before May 30, 1991; and the MSW landfill accepted waste at any time since November 8, 1987 or the landfill has additional capacity for future waste deposition. (See WAC 173-400-115 for the requirements for MSW landfills constructed, reconstructed, or modified on or after May 30, 1991.) Terms in this subsection have the meaning given them in 40 C.F.R. 60.751, except that ev-

ery use of the word "administrator" in the federal rules referred to in this subsection includes the "permitting authority."

(b) Exceptions. Any physical or operational change to an MSW landfill made solely to comply with these rules is not considered a modification or rebuilding.

(c) Standards for MSW landfill emissions.

(i) A MSW landfill having a design capacity less than 2.5 million megagrams or 2.5 million cubic meters must comply with the requirements of 40 C.F.R. 60.752(a) in addition to the applicable requirements specified in this section.

(ii) A MSW landfill having design capacity equal to or greater than 2.5 million megagrams and 2.5 million cubic meters must comply with the requirements of 40 C.F.R. 60.752(b) in addition to the applicable requirements specified in this section.

(d) Recordkeeping and reporting. A MSW landfill must follow the recordkeeping and reporting requirements in 40 C.F.R. 60.757 (submission of an initial design capacity report) and 40 C.F.R. 60.758 (recordkeeping requirements), as applicable, except as provided for under (d) (i) and (ii).

(i) The initial design capacity report for the facility is due before September 20, 2001.

(ii) The initial nonmethane organic compound (NMOC) emissions rate report is due before September 20, 2001.

(e) Test methods and procedures.

(i) A MSW landfill having a design capacity equal to or greater than 2.5 million megagrams and 2.5 million cubic meters must calculate the landfill nonmethane organic compound emission rates following the procedures listed in 40 C.F.R. 60.754, as applicable, to determine whether the rate equals or exceeds 50 megagrams per year.

(ii) Gas collection and control systems must meet the requirements in 40 C.F.R. 60.752 (b) (2) (ii) through the following procedures:

(A) The systems must follow the operational standards in 40 C.F.R. 60.753.

(B) The systems must follow the compliance provisions in 40 C.F.R. 60.755 (a) (1) through (a) (6) to determine whether the system is in compliance with 40 C.F.R. 60.752 (b) (2) (ii).

(C) The system must follow the applicable monitoring provisions in 40 C.F.R. 60.756.

(f) Conditions. Existing MSW landfills that meet the following conditions must install a gas collection and control system:

(i) The landfill accepted waste at any time since November 8, 1987, or the landfill has additional design capacity available for future waste deposition;

(ii) The landfill has design capacity greater than or equal to 2.5 million megagrams or 2.5 million cubic meters. The landfill may calculate design capacity in either megagrams or cubic meters for comparison with the exception values. Any density conversions shall be documented and submitted with the report; and

(iii) The landfill has a nonmethane organic compound (NMOC) emission rate of 50 megagrams per year or greater.

(g) Change in conditions. After the adoption date of this rule, a landfill that meets all three conditions in (e) of this subsection must comply with all the requirements of this section within thirty months of the date when the conditions were met. This change will usually occur because the NMOC emission rate equaled or exceeded the rate of 50 megagrams per year.

(h) Gas collection and control systems.

(i) Gas collection and control systems must meet the requirements in 40 C.F.R. 60.752 (b) (2) (ii).

(ii) The design plans must be prepared by a licensed professional engineer and submitted to the permitting authority within one year after the adoption date of this section.

(iii) The system must be installed within eighteen months after the submittal of the design plans.

(iv) The system must be operational within thirty months after the adoption date of this section.

(v) The emissions that are collected must be controlled in one of three ways:

(A) An open flare designed and operated according to 40 C.F.R. 60.18;

(B) A control system designed and operated to reduce NMOC by 98 percent by weight; or

(C) An enclosed combustor designed and operated to reduce the outlet NMOC concentration to 20 parts per million as hexane by volume, dry basis to three percent oxygen, or less.

(i) Air operating permit.

(i) A MSW landfill that has a design capacity less than 2.5 million megagrams or 2.5 million cubic meters on January 7, 2000, is not subject to the air operating permit regulation, unless the landfill is subject to chapter 173-401 WAC for some other reason. If the design capacity of an exempted MSW landfill subsequently increases to equal or exceed 2.5 million megagrams or 2.5 million cubic meters by a change that is not a modification or reconstruction, the landfill is subject to chapter 173-401 WAC on the date the amended design capacity report is due.

(ii) A MSW landfill that has a design capacity equal to or greater than 2.5 million megagrams or 2.5 million cubic meters on January 7, 2000, is subject to chapter 173-401 WAC beginning on the effective date of this section. (Note: Under 40 C.F.R. 62.14352(e), an applicable MSW landfill must have submitted its application so that by April 6, 2001, the permitting authority was able to determine that it was timely and complete. Under 40 C.F.R. 70.7(b), no source may operate after the time that it is required to submit a timely and complete application.)

(iii) When a MSW landfill is closed, the owner or operator is no longer subject to the requirement to maintain an operating permit for the landfill if the landfill is not subject to chapter 173-401 WAC for some other reason and if either of the following conditions are met:

(A) The landfill was never subject to the requirement for a control system under 40 C.F.R. 62.14353; or

(B) The landfill meets the conditions for control system removal specified in 40 C.F.R. 60.752 (b) (2) (v).

**(7) Municipal solid waste landfills that commenced construction on or before July 17, 2014, and have not been modified or reconstructed since July 17, 2014.** A municipal solid waste landfill that commenced construction on or before July 17, 2014, and has not been modified or reconstructed since July 17, 2014, must comply with the requirements in 40 C.F.R. Part 62, Subpart 000 (in effect on the date in WAC 173-400-025).

AMENDATORY SECTION (Amending WSR 16-12-099, filed 5/31/16, effective 7/1/16)

**WAC 173-400-115 Standards of performance for new sources. NSPS.** Standards of performance for new sources are called New Source Performance Standards, or NSPS.

(1) **Adoption of federal rules.**

(a) 40 C.F.R. Part 60 and Appendices (in effect on the date in WAC 173-400-025) are adopted. Exceptions are listed in (b) of this subsection.

(b) Exceptions to adopting 40 C.F.R. Part 60.

(i) The term "administrator" in 40 C.F.R. Part 60 includes the permitting authority.

(ii) The following sections and subparts of 40 C.F.R. Part 60 are not adopted:

(A) 40 C.F.R. 60.5 (determination of construction or modification);

(B) 40 C.F.R. 60.6 (review of plans);

(C) 40 C.F.R. Part 60, subpart B (Adoption and Submittal of State Plans for Designated Facilities), and subparts C, Cb, Cc, Cd, Ce, Cf, BBBB, DDDD, FFFF, MMMM, ((UUUU)) and UUUUa (emission guidelines); and

(D) 40 C.F.R. Part 60, Appendix G, Provisions for an Alternative Method of Demonstrating Compliance With 40 C.F.R. 60.43 for the Newton Power Station of Central Illinois Public Service Company.

Note: Refer to WAC 173-400-050 and 173-400-070 for adoption of federal rules that implement emission guidelines.

(2) Where EPA has delegated to the permitting authority, the authority to receive reports under 40 C.F.R. Part 60, from the affected facility in lieu of providing such report to EPA, the affected facility is required to provide such reports only to the permitting authority unless otherwise requested in writing by the permitting authority or EPA.

Note: Under RCW 80.50.020(14), larger energy facilities subject to subparts D, Da, GG, J, K, Kb, Y, KKK, LLL, and QQQ are regulated by the energy facility site evaluation council (EFSEC).

AMENDATORY SECTION (Amending WSR 16-12-099, filed 5/31/16, effective 7/1/16)

**WAC 173-400-720 Prevention of significant deterioration (PSD).**

(1) No major stationary source or major modification to which the requirements of this section apply is authorized to begin actual construction without having received a PSD permit.

(2) **Early planning encouraged.** In order to develop an appropriate application, the source should engage in an early planning process to assess the needs of the facility. An opportunity for a preapplication meeting with ecology is available to any potential applicant.

(3) **Enforcement.** Ecology or the permitting authority with jurisdiction over the source under chapter 173-401 WAC, the Operating permit regulation, shall:

(a) Receive all reports required in the PSD permit;

(b) Enforce the requirement to apply for a PSD permit when one is required; and

(c) Enforce the conditions in the PSD permit.

(4) **Applicable requirements.**

(a) A PSD permit must assure compliance with the following requirements:

(i) WAC 173-400-113 (1) through (4);

(ii) WAC 173-400-117 - Special protection requirements for federal Class I areas;

(iii) WAC 173-400-200;

(iv) WAC 173-400-205;

(v) Allowable emission limits established under WAC 173-400-081 must also meet the criteria of 40 C.F.R. 52.21 (k) (1) and 52.21 (p) (1) through (4) (in effect on the date in WAC 173-400-025); and

(vi) The following subparts of 40 C.F.R. 52.21 (in effect on the date in WAC 173-400-025) are adopted. Exceptions are listed in (b) (i), (ii), (iii), and (iv) of this subsection:

Section	Title
40 C.F.R. 52.21 (a)(2)	Applicability Procedures.
40 C.F.R. 52.21 (b)	Definitions, except the definition of "secondary emissions."
40 C.F.R. 52.21 (c)	Ambient air increments.
40 C.F.R. 52.21 (d)	Ambient air ceilings.
40 C.F.R. 52.21 (h)	Stack heights.
40 C.F.R. 52.21 (i)	Review of major stationary sources and major modifications - Source applicability and exemptions.
40 C.F.R. 52.21 (j)	Control technology review.
40 C.F.R. 52.21 (k)	Source impact analysis.
40 C.F.R. 52.21 (l)	Air quality models.
40 C.F.R. 52.21 (m)	Air quality analysis.
40 C.F.R. 52.21 (n)	Source information.
40 C.F.R. 52.21 (o)	Additional impact analysis.
40 C.F.R. 52.21 (p)(1) through (4)	Sources impacting federal Class I areas - Additional requirements
40 C.F.R. 52.21 (r)	Source obligation.
40 C.F.R. 52.21 (v)	Innovative control technology.
40 C.F.R. 52.21 (w)	Permit rescission.
40 C.F.R. 52.21 (aa)	Actuals Plantwide Applicability Limitation.

(b) Exceptions to adopting 40 C.F.R. 52.21 by reference.

(i) Every use of the word "administrator" in 40 C.F.R. 52.21 means ecology except for the following:

(A) In 40 C.F.R. 52.21 (b) (17), the definition of federally enforceable, "administrator" means the EPA administrator.

(B) In 40 C.F.R. 52.21 (1) (2), air quality models, "administrator" means the EPA administrator.

(C) In 40 C.F.R. 52.21 (b) (43) the definition of prevention of significant deterioration program, "administrator" means the EPA administrator.

(D) In 40 C.F.R. 52.21 (b) (48) (ii) (c) related to regulations promulgated by the administrator, "administrator" means the EPA administrator.

(E) In 40 C.F.R. 52.21 (b) (50) (i) related to the definition of a regulated NSR pollutant, "administrator" means the EPA administrator.

(F) In 40 C.F.R. 52.21 (b) (37) related to the definition of re-powering, "administrator" means the EPA administrator.

(G) In 40 C.F.R. 52.21 (b) (51) related to the definition of reviewing authority, "administrator" means the EPA administrator.

(ii) Each reference in 40 C.F.R. 52.21(i) to "paragraphs (j) through (r) of this section" is amended to state "paragraphs (j) through (p) (1), (2), (3) and (4) of this section, paragraph (r) of this section, WAC 173-400-720, and 173-400-730."

(iii) The following paragraphs replace the designated paragraphs of 40 C.F.R. 52.21:

(A) ~~((In 40 C.F.R. 52.21 (b) (1) (i) (a) and (b) (1) (iii) (h), the size threshold for municipal waste incinerators is changed to 50 tons of refuse per day.~~

~~(B) 40 C.F.R. 52.21 (b) (23) (i) After the entry for municipal solid waste landfills emissions, add Ozone Depleting Substances: 100 tpy.~~

~~(C) 40 C.F.R. 52.21(c) after the effective date of EPA's incorporation of this section into the Washington state implementation plan, the concentrations listed in WAC 173-400-116(2) are excluded when determining increment consumption.~~

(D) In (a) (2) (iv) (c): "Actual-to-projected-actual applicability test for projects that only involve existing emissions units. A significant emissions increase of a regulated NSR pollutant is projected to occur if the sum of the increase between the projected actual emissions (as defined in paragraph (b) (41) of this section) and the baseline actual emissions (as defined in paragraphs (b) (48) (i) and (ii) of this section), for each existing emissions unit, equals or exceeds the significant amount for that pollutant (as defined in paragraph (b) (23) of this section)."

(B) In (a) (2) (iv) (d): "Actual-to-potential test for projects that only involve construction of a new emissions unit(s). A significant emissions increase of a regulated NSR pollutant is projected to occur if the sum of the increase between the potential to emit (as defined in paragraph (b) (4) of this section) from each new emissions unit following completion of the project and the baseline actual emissions (as defined in paragraph (b) (48) (iii) of this section) of these units before the project equals or exceeds the significant amount for that pollutant (as defined in paragraph (b) (23) of this section)."

(C) In (a) (2) (iv) (f): "Hybrid test for projects that involve multiple types of emissions units. A significant emissions increase of a regulated NSR pollutant is projected to occur if the sum of the increase for each emissions unit, using the method specified in paragraphs (a) (2) (iv) (c) and (d) of this section as applicable with respect to each emissions unit, equals or exceeds the significant amount for that pollutant (as defined in paragraph (b) (23) of this section)."

(D) In 40 C.F.R. 52.21 (b) (1) (i) (a) and (b) (1) (iii) (h), the size threshold for municipal waste incinerators is changed to 50 tons of refuse per day.

(E) 40 C.F.R. 52.21 (b) (23) (i) after the entry for municipal solid waste landfills emissions, add Ozone Depleting Substances: 100 tpy.

(F) 40 C.F.R. 52.21(c) after the effective date of EPA's incorporation of this section into the Washington state implementation plan, the concentrations listed in WAC 173-400-116(2) are excluded when determining increment consumption."

(G) 40 C.F.R. 52.21 (r) (6)

"The provisions of this paragraph (r) (6) apply with respect to any regulated NSR pollutant from projects at an existing emissions unit at a major stationary source (other than



projects at a source with a PAL) in circumstances where there is a reasonable possibility that a project that is not a part of a major modification may result in a significant emissions increase of such pollutant and the owner or operator elects to use the method specified in paragraphs 40 C.F.R. 52.21 (b) (41) (ii) (a) through (c) for calculating projected actual emissions.

- (i) Before beginning actual construction of the project, the owner or operator shall document and maintain a record of the following information:
  - (a) A description of the project;
  - (b) Identification of the emissions unit(s) whose emissions of a regulated NSR pollutant could be affected by the project; and
  - (c) A description of the applicability test used to determine that the project is not a major modification for any regulated NSR pollutant, including the baseline actual emissions, the projected actual emissions, the amount of emissions excluded under paragraph 40 C.F.R. 52.21 (b) (41) (ii) (c) and an explanation for why such amount was excluded, and any netting calculations, if applicable.
- (ii) The owner or operator shall submit a copy of the information set out in paragraph 40 C.F.R. 52.21 (r) (6) (i) to the permitting authority before beginning actual construction. This information may be submitted in conjunction with any NOC application required under the provisions of WAC 173-400-110. Nothing in this paragraph (r) (6) (ii) shall be construed to require the owner or operator of such a unit to obtain any PSD determination from the permitting authority before beginning actual construction.
- (iii) The owner or operator shall monitor the emissions of any regulated NSR pollutant that could increase as a result of the project and that is emitted by any emissions unit identified in paragraph 40 C.F.R. 52.21 (r) (6) (i) (b); and calculate and maintain a record of the annual emissions, in tons per year on a calendar year basis, for a period of 5 years following resumption of regular operations after the change, or for a period of 10 years following resumption of regular operations after the change if the project increases the design capacity of or potential to emit that regulated NSR pollutant at such emissions unit.
- (iv) The owner or operator shall submit a report to the permitting authority within 60 days after the end of each year during which records must be generated under paragraph 40 C.F.R. 52.21 (r) (6) (iii) setting out the unit's annual emissions during the calendar year that preceded submission of the report.

- (v) The owner or operator shall submit a report to the permitting authority if the annual emissions, in tons per year, from the project identified in paragraph 40 C.F.R. 52.21 (r) (6) (i), exceed the baseline actual emissions (as documented and maintained pursuant to paragraph 40 C.F.R. 52.21 (r) (6) (i) (c)), by a significant amount (as defined in paragraph 40 C.F.R. 52.21 (b) (23)) for that regulated NSR pollutant, and if such emissions differ from the preconstruction projection as documented and maintained pursuant to paragraph 40 C.F.R. 52.21 (r) (6) (i) (c). Such report shall be submitted to the permitting authority within 60 days after the end of such year. The report shall contain the following:
  - (a) The name, address and telephone number of the major stationary source;
  - (b) The annual emissions as calculated pursuant to paragraph (r) (6) (iii) of this section; and
  - (c) Any other information that the owner or operator wishes to include in the report (e.g., an explanation as to why the emissions differ from the preconstruction projection).
- (vi) A "reasonable possibility" under this subsection occurs when the owner or operator calculates the project to result in either:
  - (a) A projected actual emissions increase of at least fifty percent of the amount that is a "significant emissions increase," (without reference to the amount that is a significant net emissions increase), for the regulated NSR pollutant; or
  - (b) A projected actual emissions increase that, added to the amount of emissions excluded under the definition of projected actual emissions sums to at least fifty percent of the amount that is a "significant emissions increase," (without reference to the amount that is a significant net emissions increase), for the regulated NSR pollutant. For a project for which a reasonable possibility occurs only within the meaning of (r) (6) (vi) (b) of this subsection, and not also within the meaning of (r) (6) (vi) (a) of this subsection, then the provisions of (r) (6) (vi) (ii) through (v) of this subsection do not apply to the project."

~~((E))~~ (H) 40 C.F.R. 52.21 (r) (7) "The owner or operator of the source shall submit the information required to be documented and maintained pursuant to paragraphs 40 C.F.R. 52.21 (r) (6) (iv) and (v) annually within 60 days after the anniversary date of the original analysis. The original analysis and annual reviews shall also be available for review upon a request for inspection by the permitting authority or the general public pursuant to the requirements contained in 40 C.F.R. 70.4 (b) (3) (viii)."

~~((F))~~ (I) 40 C.F.R. 52.21 (aa) (2) (ix) "PAL permit means the PSD permit, an ecology issued order of approval issued under WAC 173-400-110, or regulatory order issued under WAC 173-400-091 issued by ecology that establishes a PAL for a major stationary source."

~~((G))~~ (J) 40 C.F.R. 52.21 (aa) (5) "Public participation requirements for PALs. PALs for existing major stationary sources shall be established, renewed, or expired through the public participation process in WAC 173-400-171. A request to increase a PAL shall be pro-

cessed in accordance with the application processing and public participation process in WAC 173-400-730 and 173-400-740."

~~((H))~~ (K) 40 C.F.R. 52.21 (aa)(9)(i)(b) "Ecology, after consultation with the permitting authority, shall decide whether and how the PAL allowable emissions will be distributed and issue a revised order, order of approval or PSD permit incorporating allowable limits for each emissions unit, or each group of emissions units, as ecology determines is appropriate."

~~((I))~~ (L) 40 C.F.R. 52.21 (aa)(14) "Reporting and notification requirements. The owner or operator shall submit semiannual monitoring reports and prompt deviation reports to the permitting authority in accordance with the requirements in chapter 173-401 WAC. The reports shall meet the requirements in paragraphs 40 C.F.R. 52.21 (aa)(14)(i) through (iii)."

~~((J))~~ (M) 40 C.F.R. 52.21 (aa)(14)(ii) "Deviation report. The major stationary source owner or operator shall promptly submit reports of any deviations or exceedance of the PAL requirements, including periods where no monitoring is available. A report submitted pursuant to WAC 173-401-615 (3)(b) and within the time limits prescribed shall satisfy this reporting requirement. The reports shall contain the information found at WAC 173-401-615(3)."

(iv) The following provisions in 40 C.F.R. 52.21 ~~((r)(2) is)~~ are not adopted: (a)(2)(iv)(g) and (r)(2).